

High-purity microwave signal from a dual-frequency semiconductor laser for CPT atomic clocks

P. Dumont¹, J.-M. Danet², F. A. Camargo¹, D. Holleville², S. Guerandel², G. Baili³, L. Morvan³, G. Pillet³, D. Dolfi³, I. Gozhyk^{1,4}, G. Beaudoin⁴, I. Sagnes⁴, P. Georges¹, G. Lucas-Leclin¹

¹ Laboratoire Charles Fabry, Institut d'Optique, CNRS, Univ Paris-Sud 11, Palaiseau, France

² LNE-SYRTE, Observatoire de Paris, CNRS, UPMC, Paris, France

³Thales Research & Technology, Palaiseau, France

⁴Laboratoire de Photonique et de Nanostructures, CNRS UPR20, Marcoussis, France

Email: paul.dumont@institutoptique.fr

Coherent population trapping (CPT) is an interesting technique for the development of compact atomic frequency references¹; it relies on the excitation of alkali atoms by two phase-coherent laser fields. We describe the design and operation of an innovating dual-frequency laser source dedicated to Cs CPT atomic clocks, based on the direct dual-frequency and dual-polarization operation of an optically-pumped semiconductor laser (OPSL) at $\lambda = 852.14$ nm.

An OPSL consists in a semiconductor chip, including both high-reflection Bragg mirror and active material, placed in an external cavity and directly pumped by a high-power laser diode. The dual-frequency operation of the laser is generated by intracavity birefringent components. They induce a controllable phase anisotropy within the laser cavity and force the emission on two cross-polarized longitudinal modes². The laser emission is tuned at the Cs D₂ line and the frequency difference between the two modes is tunable in the microwave range.

The stabilization of the dual-frequency laser operation is achieved through two servo-loops. The optical frequency of one laser line is locked onto a Cs transition through correction of cavity length with a piezo-transducer. The frequency difference between the two laser lines is locked onto a stable RF synthesizer through feedback to an intracavity electro-optic modulator. The additive contribution of the laser and the phase-lock loop (PLL) to the beatnoise phase noise is 10^{-10} rad²/Hz for frequencies below 3 kHz, which assesses the high purity of the microwave beatnote signal. The relative intensity noise (RIN) at each laser line is flat up to 1 MHz thanks to the lack of relaxation oscillations in OPSL. It is limited by pump intensity noise, at a level of 10^{-11} Hz⁻¹.

Finally, we have estimated the short-term clock stability that would be achieved with our laser source on a CPT Ramsey-like atomic clock³; a relative stability in the range of $3 \cdot 10^{-13}$ over 1 s seems a realistic target with a reduction of the RIN contribution.




Fig. 1: Power spectrum density of the beatnote phase noise for the residual contribution (Laser + PLL) and the RF synthesizer contribution.

¹ J. Vanier, “Atomic clocks based on coherent population trapping: a review,” *Appl. Phys. B*, vol. 81, no. 4, pp. 421–442, Jul. 2005.

² F. A. Camargo et al, “Coherent Dual-Frequency Emission of a Vertical External-Cavity Semiconductor Laser at the Cesium D₂ Line,” *IEEE Photonics Technol. Lett.*, vol. 24, no. 14, pp. 1218–1220, 2012.

³ J.-M. Danet et al, “Dick effect in a pulsed atomic clock using coherent population trapping”, to be published in *IEEE Ultrason. Ferroelectr. Freq. Control*, 2014.