

# Optical cavity acceleration sensitivity reduction via feedforward correction

Ross A. Williams<sup>1</sup>, Sean Donnellan<sup>1</sup>, Teresa I. Ferreiro<sup>1</sup>, Ian R. Hill<sup>1</sup>, Geoffrey P. Barwood<sup>1</sup>, Patrick Gill<sup>1</sup>.

<sup>1</sup>Time and Frequency Group, National Physical Laboratory, Teddington, United Kingdom

Email: [ross.williams@npl.co.uk](mailto:ross.williams@npl.co.uk)

Laser frequency stabilization to high finesse optical cavities is a key enabling technology for optical frequency standards, ultra-low-noise microwave synthesis, and exploring fundamental physics. NPL's cubic cavity<sup>1</sup> has demonstrated world-leading passive acceleration sensitivities, a crucial characteristic required for ultra-stable optical cavities to succeed beyond a laboratory setting. A recently developed technique to further improve the performance of optical cavities in real-world environments is the real-time feedforward correction of perturbations to the cavity<sup>2</sup>. Such a technique requires: (i) characterizing the response of a cavity to inertial forces; (ii) actively sensing the acceleration experienced by the cavity, then calculating the induced change in cavity length and correcting for it.

We report on the real-time cancellation of acceleration-induced frequency perturbations of a laser locked to a shaken cubic cavity. The feedforward-correction system is based around an array of accelerometers centered on the high-finesse optical cavity and a FPGA for rapid calculation of the frequency correction, which is applied via an AOM. A 32 dB reduction in the acceleration-induced laser frequency noise power spectral density is achieved.

Acknowledgements: This work is supported by the UK and European Space Agencies, the National Physical Laboratory Strategic Research Programme, and by the European Metrology Research Programme (EMRP). The EMRP is jointly funded by the EMRP participating countries within EURAMET and the European Union.




Fig. 1: Power spectral density of the laser frequency, with and without the real-time feedforward correction engaged. A 32 dB reduction in the PSD at the shaking frequency (6 Hz) is observed. Inset: the time-series data showing the cancellation of the driven low-frequency oscillation in the laser frequency.

<sup>1</sup> S. Webster and P. Gill, “Force-insensitive optical cavity”, *Optics Letters*, vol. 36, p. 3572-3574, 2011.

<sup>2</sup> D. R. Leibrandt *et al*, “Cavity-stabilized laser with acceleration sensitivity below  $10^{-12} \text{ g}^{-1}$ ”, *Phys. Rev. A*, vol. 87, p. 023829, 2013.