

# Compact Atomics Package and Integration of a Transportable Strontium Lattice Clock

Yeshpal Singh<sup>1</sup>, Lyndsie Smith<sup>1</sup>, Ole Kock<sup>1</sup>, Wei He<sup>1</sup>, Dariusz Swierad<sup>1</sup>, Kai Bongs<sup>1</sup> and the SOC2 team<sup>2</sup>

<sup>1</sup>Department of Physics and Astronomy, University of Birmingham, Edgbaston Park Road, Birmingham B15 2TT, UK

<sup>2</sup>Heinrich-Heine-Universität Düsseldorf, Germany

Physikalisch-Technische-Bundesanstalt, Germany

Leibniz Universität Hannover, Germany

Observatoire de Paris, France; Università di Firenze,

National Physical Laboratory Teddington, the United Kingdom

TOPTICA Photonics AG, Germany; EADS Astrium Friedrichshafen, Germany

Menlo Systems GmbH, Germany; Kayser-Threde GmbH, Germany; Kayser Italia S.r.l., Italy

Centre Suisse d'Electronique et de Microtechnique SA, Switzerland ; Université de Neuchâtel,

Switzerland ; Ecoles Polytechniques Fédérales Lausanne, Switzerland

Istituto Nazionale di Ricerca Metrologica, Italy

Email: [y.singh.1@bham.ac.uk](mailto:y.singh.1@bham.ac.uk)

With the rapidly improving performance of optical clocks, in the future, most applications requiring the highest accuracy will require these systems. The unprecedented accuracy in time promises new applications like relativistic geodesy which might benefit the exploration of oil and minerals, fundamental tests of general relativity and synchronization for long base line astronomical interferometry, deep space navigation. In the framework of the research project SOC2: "Towards Neutral-atom Space Optical Clocks" funded by the EU 7<sup>th</sup> framework programme (FP7/2007-2013) under grant agreement n. 263500, with the main aim of developing demonstrators of transportable lattice clocks with  $5 \times 10^{-17}$  relative frequency accuracy [1], we are reporting on the realization of a very compact, light and energy efficient atomics package for a Sr clock prototype. At the heart of the atomics package is a 3D MOT chamber (Fig.1) which can be loaded either with a permanent magnet Zeeman slower or with a 2D MOT facility. We will also report on the integration of different components (e.g. lasers, FSS unit) of the SOC2 apparatus, which have been developed by other partners of the consortium and have been transported to us at the University of Birmingham from the University of Florence. The total budget of the system will be  $<10^1$ ,  $<10^{-10}$  mbar,  $<20$  kg [2].

## References:

[1] S. Schiller et al. "Towards Neutral-atom Space Optical Clocks (SOC2): Development of high-performance transportable and breadboard optical clocks and advanced subsystems" on "Let's embrace space, volume II" **45**, 452-463 (2012). ISBN 978-92-79-22207-8.

[2] [www.soc2.eu](http://www.soc2.eu)




Fig. 1: Trapped Sr atoms in our 3D MOT chamber.